

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 November 2005 (10.11.2005)

PCT

(10) International Publication Number
WO 2005/106231 A1

(51) International Patent Classification⁷: **F02D 41/40**,
F02M 57/02, 59/10, 47/02

(21) International Application Number:
PCT/IB2005/001144

(22) International Filing Date: 28 April 2005 (28.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-135088 30 April 2004 (30.04.2004) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA?** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FUTONAGANE, Yoshinori** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha,


1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP). **OMAE, Kazuhiro** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP). **HOTTA, Yoshihiro** [JP/JP]; c/o Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi 480-1192 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: **PRESSURE BOOSTING COMMON RAIL FUEL INJECTION APPARATUS AND FUEL INJECTION CONTROL METHOD THEREFOR**



(57) Abstract: A fuel injection valve (10) with a pressure boosting unit is provided in an engine (1), and boosted pressure fuel injection is performed by increasing a pressure of fuel supplied to a fuel injection valve from a common rail (3). An ECU (20) decides a pressure boosting period that is defined as a time period from when the pressure of the fuel starts to be boosted until when the fuel injection is started using a numerical table in which a fuel injection amount and an engine rotational speed are used as parameters, and sets fuel injection control parameters such as a fuel injection period and pressure boosting starting timing, based on the pressure boosting period. Since the fuel injection control parameters are set based on the pressure boosting period, the control that is performed when the boosted pressure fuel injection is performed is simplified.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.